

GOES TERROX 400L T3B '24

Geoes

DESCRIERE

GOES is an international group specialized in the design, development and distribution of off-road vehicles. This recognized French brand has perfected itself over the years, becoming one of the world leaders in the off-road vehicle market. In January 2024, Zhejiang CFMOTO Power Co., Ltd (CFMOTO) announced the completion of the 100% acquisition of Goes. With support from the Chinese company, GOES will expand its product portfolios to meet the needs of a wider customer base and optimize its current distribution networks.

CFMOTO CFORCE GOES 400L is a last generation ATV that promises to offer performance on the toughest terrains. A 4x4 partner with two seats perfect for leisure, but also to help you with various utilitarian tasks. Transport capacity: two seats.

Technical specifications:

- engine: 1 cylinder, 400 cc, liquid cooled, 4 strokes, SOHC, 4 valves, EFI
- maximum power: 20.7 kW / 7250 rpm
- maximum torque: 31.1 Nm / 5500 rpm
- electric start
- CVT automatic box
- 2WD/4WD selectable traction
- independent front suspension, double arm type A
- independent rear suspension, double arm type A
- front/rear shock absorbers: oil shock absorber with spiral spring
- front wheel side brake + rear wheel central axle brake + central axle parking
- USB port
- 12 inch rims
- 25 inch tires
- front and rear bumpers
- rear compartment for storing tools
- ground clearance 250 mm
- height of 530 mm
- maximum load capacity: 200 kg
- hook towing capacity: 300 kg
- color schemes: Ghost Grey, Pearl Injected Black.

This vehicle is driven with a category B license.

T3b approval (registration at the town hall).





GENERAL

Matriculate: DA Year: 2024 Driving licence categories: B Homologation: Tractor



Engine: 1 cylinders, 4 valve ,4 strokes,SOHC Capacity: 400 cmc Fuel: Petrol Gearbox: CVT Fuel tank capacity: 14 I Cooling: liquid Ignition: Electric Homologated power: 28.2 HP Constructive power: 27.7 HP



Length: 2390 mm Width: 1100 mm Height: 1435 mm Curb weight: 382 KG Seat height: 530 mm Ground clearance: 250 mm



Front suspension system: Double A-arm Independent suspension

Rear suspension system: Double A-arm Independent suspension

Front brake: Hydraulic disc brakes Front tyre: AT25×8.00-12" Rear tyre: AT25×10.00-12 "